New Instruments and Research for Analysis

## **UENUS** SERIES 300

METHANE&NON-METHANE HYDROCARBON ANALYZER IN LOW CONCENTRATION.

NIRA Analyzer Mod. **VENUS 301** is a sensitive instrument specifically designed to automatically measure traces of organic volatile composites in air, able to separate methane and non-methane components in one single analysis.



**Denus 300** 

It is designed to simplify typical monitoring problems, carrying out the task in cabins or mobile units maintaining the typical sensitivity and selectivity of the laboratory instruments.

This instrument separate organic volatile compounds trough packed columns and detect them with FID. With the VENUS 301, N.I.R.A. gives coherent and complete results to those who value air quality: urban vehicular traffic pollution monitoring in fixed or on mobile units; industrial or residential area monitoring near industrial plants.

## BENEFITS

- Flame ionization detector: enhanced linearity, reproducibility, reliability and can be used in cabins.
- Sampling membrane valves: they can work for years at a high temperature without any maintenance.
- > Optimized pneumatics: an automatic electronic pressures and temperatures monitoring system is incorporated in a traditional pneumatic circuit, this allow easier interface and performances optimization.
- > Sampling pump: integrated pump.
- > Chromatographic separation: through long life packed columns.
- > Automatic injection system.
- Hermetic detectors with channeled vent: they can be used in any area, even in controlled atmospheres.
- > FID auto diagnostic interlocked with hydrogen flow stop.
- > High precision thermostatic oven for a high resolution separation.

## "PC EMBEDDED" TECHNOLOGY

- Allows the total visibility in every analytical step;
- Increase the quality of chromatograms thanks to an LCD/TFT display and a real time analysis control;
- Increased sampling accuracy and precise chromatogram elaboration;
- Accurate data elaboration: integration, trend recording, and history of all anomalies that may occur;

• Graphic and numeric data re-loading off-line;

www.nirainstruments.it

- Continuous checking of: operating parameters, analysis and conditioning;
- Trends recordings;
- Auto-diagnostic;

## TECHNICAL SPECIFICATION

ANALYZED COMPONENTS	VOC as methane & non methane components
RANGES (SELECTABLE)	0-5; 0-10; 0-100; 0-1000ppm
RESPONSE TIME	120 seconds
NOISE	< 0.1 ppm
SENSIBILITY	< 0.2 ppm
ZERO DRIFT	Compensated
SPAN DRIFT WITHIN 24H (MAX SENSIBILITY)	< 1%
ACCURACY	1%fs
LINEARITY	1%fs
REPEATABILITY	< 1%fs
TEMPERATURE WORKING RANGE	+5; +40°C
HYDROGEN	3 bar, 40ml/min.
AIR	4 bar, 350ml/min.
DISPLAY INTERFACE	LCD - 10.4"
ANALOGIC OUTPUT	0-10V; 4-20mA
SERIAL OUTPUT (OTHERS IN OPTION)	RS 232
POWER SUPPLY	230V; 110V (in option)
DIMENSIONS	450x270x600mm (L x W x H)
WEIGHT	20 kg

